

General Purpose Wheel Chocks

10 - 35 Ton Vehicles GVW (Gross Vehicle Operating Weight)

- Light weight with tough urethane construction
- Range of wheel chocks rated for general purpose vehicles with gross operating weights from 10 Ton (20,000 lbs) to 35 Ton (70,000 lbs) and tyre sizes from 35" (88.90cm) to 46" (116.84cm)
- 3rd party tested for compliance
- Complies with NFPA 1901 and NFPA 1906 Standards
- Resistant to oils, fuels and solvents
- Built-in carrying handle
- High visibility colour used for safety
- Holes for rope, chains & mounting brackets

WC-UO300 / WC-UO300-2R

Vehicles up to 10 Ton (20,000 lbs) GVW and tyre sizes up to 35" (88.90cm)



WC-UO300



WC-UO300



WC-UO300-2R

Part No.	Length	Width	Height	Weight	Tyre Size	GVW
WC-UO300	7.5" (19.05cm)	7" (17.78cm)	6" (15.24cm)	2.2 lbs (1.00kg)	35" (88.90cm)	10 Ton* (20,000 lbs)
WC-UO300-2R	7.5" (19.05cm)	7" (17.78cm)	6" (15.24cm)	5.5 lbs (2.49kg)	35" (88.90cm)	10 Ton* (20,000 lbs)

2R - Set with rope

* Minimum of 2 chocks

WC-UO400 / WC-UO400-2R

Vehicles up to 15 Ton (30,000 lbs) GVW and tyre sizes up to 35" (88.90cm)



WC-UO400



WC-UO400



WC-UO400-2R

Part No.	Length	Width	Height	Weight	Tyre Size	GVW
WC-UO400	8.5" (21.59cm)	7.5" (19.05cm)	6.25" (15.875cm)	2 lbs (0.91kg)	35" (88.90cm)	15 Ton* (30,000 lbs)
WC-UO400-2R	8.5" (21.59cm)	7.5" (19.05cm)	6.25" (15.875cm)	5 lbs (2.27kg)	35" (88.90cm)	15 Ton* (30,000 lbs)

2R - Set with rope

* Minimum of 2 chocks

WC-UO500

Vehicles up to 25 Ton (50,000 lbs) GVW and tyre sizes up to 32" (81.28cm)



WC-UO500



WC-UO500

Part No.	Length	Width	Height	Weight	Tyre Size	GVW
WC-UO500	10" (25.40cm)	8.5" (21.59cm)	5" (12.70cm)	4.5 lbs (2.04kg)	32" (81.28cm)	25 Ton* (50,000 lbs)

* Minimum of 2 chocks

Testing and qualification is required for individual vehicle for correct product selection to meet site requirements.

Advised GVW is a guide only. This will vary due to environmental factors. Please complete an adequate risk assessment before using chocks. Do not use chocks if chocks are damaged.

Authorised Importer and Master Distributor





General Purpose Wheel Chocks

10 - 35 Ton Vehicles GVW (Gross Vehicle Operating Weight)

- Light weight with tough urethane construction
- Range of wheel chocks rated for general purpose vehicles with gross operating weights from 10 Ton (20,000 lbs) to 35 Ton (70,000 lbs) and tyre sizes from 35" (88.90cm) to 46" (116.84cm)
- 3rd party tested for compliance
- Complies with NFPA 1901 and NFPA 1906 Standards
- Resistant to oils, fuels and solvents
- Built-in carrying handle
- High visibility colour used for safety
- Holes for rope, chains & mounting brackets

WC-UO600 / WC-UO600-2R

Vehicles up to 30 Ton (60,000 lbs) GVW and tyre sizes up to 46" (116.84cm)



WC-UO600



WC-UO600



WC-UO600-2R

Part No.	Length	Width	Height	Weight	Tyre Size	GVW
WC-UO600	11.5" (29.21cm)	9" (22.86cm)	8.5" (21.59cm)	4.5 lbs (2.04kg)	46" (116.84cm)	30 Ton* (60,000 lbs)
WC-UO600-2R	11.5" (29.21cm)	9" (22.86cm)	8.5" (21.59cm)	10 lbs (4.54kg)	46" (116.84cm)	30 Ton* (60,000 lbs)

2R - Set with rope

* Minimum of 2 chocks

WC-UO650

Vehicles up to 35 Ton (70,000 lbs) GVW and tyre sizes up to 46" (116.84cm)



WC-UO650



WC-UO650

Part No.	Length	Width	Height	Weight	Tyre Size	GVW
WC-UO650	11.5" (29.21cm)	9" (22.86cm)	8.5" (21.59cm)	6 lbs (2.72kg)	46" (116.84cm)	35 Ton* (70,000 lbs)

* Minimum of 2 chocks



Authorised Importer and Master Distributor

