

# 7945 Series

## Pulse SAE Class II LED Beacon



### Description

7945 Series Pulse II LED beacons offer SAE Class II light output and Pulse8 flash operation combined with a long maintenance free service life and low amp draw, making this beacon a cost effective choice for many applications. Easily replaces old rotating or strobe beacons with the latest technology so no ongoing maintenance is required. Vacuum-Magnet models feature a 15' straight cigarette cord with switched plug.

### Features and Benefits

- 11 flash patterns
- Reinforced polypropylene base, polycarbonate lens
- Switched cigarette plug adapter (vacuum-magnet models)
- Temperature Range: -22°F to +122°F (-30°C to +50°C)

### Tech Specs

Type	LED
Voltage	12-48V DC
Amps	1.3A @ 12V DC
FPM	11
Color Options	Amber, Green, Red, Blue and Clear

Part No.	Description
7945A	Amber, 3 Bolt / 1" Pipe Mount, 12-48V DC, 1.3A
7945A-HBT	Amber, High Bond Tape Mount, 12-48V DC, 1.3A
7945A-VM	Amber, Vacuum-Mount, 12-48V DC, 1.3A
7945B	Blue, 3 Bolt / 1" Pipe Mount, 12-48V DC, 1.3A
7945B-VM	Blue, Vacuum-Mount, 12-48V DC, 1.3A
7945C	Blue, 3 Bolt / 1" Pipe Mount, 12-48V DC, 1.3A
7945C-VM	Clear, Vacuum Mount, 12-48V DC, 1.3A
7945G	Green, 3 Bolt / 1" Pipe Mount, 12-48V DC, 1.3A
7945G-VM	Green, Vacuum Mount, 12-48V DC, 1.3A
7945R	Red, 3 Bolt / 1" Pipe Mount, 12-48V DC, 1.3A
7945R-VM	Red, Vacuum-Mount, 12-48V DC, 1.3A



Authorised Importer and Master Distributor

