

7950 Series

Pulse SAE Class II LED Beacon



Description

7950 Series Pulse II LED beacons offer SAE Class II light output and Pulse8 flash operation combined with a long maintenance free service life and low amp draw, making this beacon a cost effective choice for many applications. Easily replaces old rotating or strobe beacons with the latest technology so no ongoing maintenance is required.

Tech Specs

Type	LED
Voltage	12-48V DC
Amps	1.3A @ 12V DC
FPM	11
Color Options	Amber, Blue, Clear, Green and Red

Part No. Description

7950A	Amber, 3 Bolt / 1" Pipe Mount, 12-48V DC, 1.3A
7950A-VM	Amber, Vacuum-Mount, 12-48V DC, 1.3A
7950A-HBT	Amber, Vacuum-Mount, 12-48V DC, 1.3A
7950B	Blue, 3 Bolt / 1" Pipe Mount, 12-48V DC, 1.3A
7950B-VM	Blue, Vacuum-Mount, 12-48V DC, 1.3A
7950C	Clear, 3 Bolt / 1" Pipe Mount, 12-48V DC, 1.3A
7950C-VM	Clear, Vacuum-Mount, 12-48V DC, 1.3A
7950G	Green, 3 Bolt / 1" Pipe Mount, 12-48V DC, 1.3A
7950G-VM	Green, Vacuum-Mount, 12-48V DC, 1.3A
7950R	Red, 3 Bolt / 1" Pipe Mount, 12-48V DC, 1.3A
7950R-VM	Red, Vacuum-Mount, 12-48V DC, 1.3A



Authorised Importer and Master Distributor

