

ABL RT 1500 LED Compact Work Light





20 12 7 3.5 1


Lux:





Voltage	12-24V DC
Tech	LED
Wattage	20W
Current	0.85A @ 24V DC
Lumens	1500 Lu
Operating Temperature	-40°C to +85°C
Beam Pattern	Flood, Long Range or Asymmetrical Flood
Connector	AMP 2 pin, DT 2 pin
Mounting	Pedestal, suspended
Lens Material	Hardened glass, Plastics
Dimensions (DxWxH)	3.03x3.58x5.07" inches (77x91x129mm)
Load Dump / Surge Dump	Surge: 36V continuous / ISO 7637-2 Pulse 5a
Weight	1.2 lbs (0.55kg)
IP Rating	IP68 / 69K
Polarity	Protected against reverse voltage
Salt Spray Test	ISO 9227
Vibration Resistance	15 Grms @ 24-2000Hz
Shock Resistance	60G
EMC	ISO 13766, ISO 14982, ISO 12985, CISPR25 Class 5
Warranty	4 Years

Part No. RT1500F **RT1500LR** RT1500FA

Description Flood, 1500 Lu, 12-24V DC, 0.85A @ 24V DC, 20W Long Range, 1500 Lu, 12-24V DC, 0.85A @ 24V DC, 20W Asymmetrical Flood, 1500 Lu, 12-24V DC, 0.85A @ 24V DC, 20W







Long Range



Authorised Importer and Master Distributor



APS USA

610 Gateway Center Way, Suites J & K San Diego, CA 92102 USA P: 1 619 263 4164 F: 1 619 263 6814

APS Australia U48 / 9 Vision Street, Wangara, WA 6065 Australia Phone: 61 (8) 9302 2369 Fax: 61 (8) 6305 0047

Chile Perú Brasil





Description

The ABL RT 1500 LED is a compact LED-powered work lamp. This 20W version features 6 LED bulbs and pumps out an impressive 1500 lumens. This lamp exceeds everyday demands in all applications from handling equipment to heavy vehicles.

Application

Heavy equipment, mining, construction, road and utility equipment, forestry, agriculture

Tech Specs

Voltage	12-24V DC
Tech	LED
Nattage	20W
Current	0.85A @ 24V DC
_umens	1500 Lu
Operating Temperature	-40°C to +85°C
Beam Pattern	Flood, Long Range or Asymmetrical Flood
Connector	AMP 2 pin, DT 2 pin
Mounting	Pedestal, suspended
_ens Material	Hardened glass, Plastics
Dimensions (DxWxH)	3.03x3.58x5.07" inches (77x91x129mm)
_oad Dump / Surge Dump	Surge: 36V continuous / ISO 7637-2 Pulse 5a
Weight	1.2 lbs (0.55kg)
P Rating	IP68 / 69K
Polarity	Protected against reverse voltage
Salt Spray Test	ISO 9227
/ibration Resistance	15 Grms @ 24-2000Hz
Shock Resistance	60G
EMC	ISO 13766, ISO 14982, ISO 12985, CISPR25 Class 5
Warranty	4 Years

APS: Singapore Colombia