



610 Gateway Center Way, Suites J & K San Diego, CA 92102 USA P: 1 619 263 4164 F: 1 619 263 6814 APS Australia U48 / 9 Vision Street, Wangara, WA 6065 Australia Phone: 61 (8) 9302 2369 Fax: 61 (8) 6305 0047 APS: Singapore Mexico Colombia Chile Perú







#### WHAT'S YOUR

# **APPLICATION?**

On-road or off-road, whatever your vocation, we have a solution for your noise pollution problems.



#### **OFF-ROAD QUICK SELECTION**

Large mobile equipment, difficult terrain, dirt, dust, and high noise levels make off-road job sites a challenging environment for workers. The goal is to maximize safety by providing the optimum warning signal while remaining mindful of public nuisance. ECCO offers multiple products ideally suited to specific off-road applications.

#### HEAVY-DUTY EQUIPMENT

and/or environments with high ambient noise.

\917N	87-112 dB(A)	
49070	87-107 dB(A)	))) ))
۸7070	107 dB(A)	)))
17020	102 dB(A)	10

#### LIGHT-DUTY CONSTRUCTION

Ideal for medium size off-road vehicles and/o

EA9724	77-97 dB(A)	))) ))
SA931N	82-102 dB(A)	
EA5200	97 dR(A)	30



#### ON-ROAD QUICK SELECTION

From city centers to suburban neighborhoods, delivery, utility, and public service vehicles backing in tight situations may pose a threat to pedestrians. Operators must focus on public safety while minimizing noise nuisance for residents and businesses. ECCO has your back with various solutions to suit a wide variety of on-road vehicles.

#### ELECTRIC VEHICLES

Ideal for smaller special application electric vehicles (36-8 VDC) and/or environments with mid-level ambient noise.

EA9780 77-97 dB(A) )))

#### OVER-THE-ROAD

or environments with mid-level ambient nois

SA951	77-97 dB(A)	
EA9724	77-97 dB(A)	
EA5200	97 dB(A)	
EA5050	87 dB(A)	

# THE INDUSTRY HAS STANDARDS, AND WE HAVE OURS

Meeting minimum industry standards doesn't always guarantee real-world performance, so at ECCO we choose to go above and beyond. All of our products meet or surpass applicable certifications, and where no standards exist, we develop our own. Because we take safety and quality very seriously, we hold ourselves to The ECCO Standard, a complete set of performance tests that are more stringent than regular industry requirements.

Our engineers use The ECCO
Standard to design and test our
products to withstand the most
extreme conditions, ensuring
protection against vibration,
impact, corrosion, dust, moisture,
temperature extremes, and more.
The result is a reliable product
from us which means more
up-time for our customers.



#### WHY ECCO?

- 48 years of proven quality
- ECCOLIFE™ (of vehicle) warranty for medium and heavy duty models
- IATF/TS 16949 Automotive Grade quality process certification
- SAE certified test processes and documentation support
- Independently certified and registered AMECA facility and test apparatuses
- In-house root cause analysis and quality reporting

#### LIFE TESTING IMP

## IMPACT

# ELEVATED TEMP

# THERMAL CYCLE

### WATER SPRAY

#### THE ECCO STANDARD

2,000 Hours

3 Drops, 1 Meter (On Concrete) +185°F (+85°C) For 8 Hours -40°F (-40°C) to +185°F (+85°C) For 10 Cycles 100 Liters Per Minute At 3 Meters, For 3 Minutes In addition to SAE J994 tests below

#### **SAE J994**

100 Hours

None

+185°F (+85°C) For 4 Hours -40°F (-40°C) to +185°F (+85°C) For 1 Cycle

1,000 PSI, 10 Sec Sweep, 30 Sec. Drain, for 50 Cycles



## WORLD-CLASS CUSTOMER SERVICE

Respect and relationships are at the root of everything we do at ECCO. Friendly customer service combined with the industry's leading distribution footprint means you can count on us for exceptional support and flexibility during the product selection process and throughout the life of your safety equipment.

#### QUALITY PRODUCTS

engineered to perform in rugged, real-world conditions. Industries across the globe know they can rely on us to help keep workers safe and value the ease of installation, operation, and maintenance.

#### SHORT LEAD TIMES

When you're ready to go to work, so is ECCO. Order what you need today and mount it tomorrow. No backorders and no additional wait for custom builds. Your safety and productivity are our priority.

# EASY CUSTOMIZATION

One size rarely fits all, especially when lives are on the line. That's why we deliver customizable safety solutions, from configurable lightbars to options and accessories that fit your specific vehicles and work sites.



ECCO stands behind our products. Our, no-hassle warranty is the best in the business. We take pride in successfully addressing customer concerns even after a warranty has expired. Our comprehensive warranty policy inspires trust and confidence, and has helped make the ECCO name synonymous with safety. Visit **eccoesg.com** for product warranty details.

#### THE ECCO CARE PROMISE ENSURES

that our products and our people perform to a higher standard—so that you can, too. Look to ECCO for reliability when you need it most. View our online catalog.



## WHAT ARE THE OPTIONS?

There are several decisions to be made when selecting a back-up alarm.

First, you can choose between a tonal alarm and a multi-frequency alarm. Industry experts have suggested either can provide an effective warning and each has its merits as described on the next page.

Second, you must choose an alarm with the appropriate sound pressure level (SPL). OSHA requires a reverse alarm to be audible above the surrounding noise level. If you know the ambient noise level and it remains reasonably constant then the appropriate fixed dB alarm can be selected, whether tonal or multi-frequency. The key is complying with the requirements of OSHA while selecting the lowest SPL alarm possible so as not to create a noise nuisance.

Fortunately, ECCO pioneered another solution — the Smart Alarm®, available in either tonal or multi-frequency. Smart Alarms monitor ambient noise automatically and adjust their output to 5dB above that, satisfying OSHA's requirements. Perfect for worksites with inconsistent noise or varying noise levels.

# START HERE

## **TONAL VS MULTI-FREQUENCY**

So what's the difference?

Tonal alarms emit sound at a single predominant frequency resulting in the familiar 'beep-beep' warning signal that we've all grown accustomed to. Conversely, multi-frequency alarms emit sound at multiple frequencies within a narrow band resulting in a 'shhh-shhh' warning sound. There is no scientific evidence to prove either sound is more effective than the other in a reversing vehicle application. However, there are several points of view that should be considered when choosing between the two.

# BEEP

The beep-beep sound is a familiar signal that is readily understood as a danger signal.

The sound is more piercing and therefore less likely to be masked by ambient noise such as vehicle engines.

# SHHH MULTI-FREQUENCY

Shhh-shhh is a newer sound that has been introduced as a warning signal.

The sound is perceived to be more directional.

The sound is perceived to dissipate more quickly outside the danger zone behind the vehicle.









#### SMART ALARM® MULTI-FREQUENCY **SURFACE MOUNT**

**VOLTS** 

12-48

12-48

12-24

12-24

12-24

12-24

12-24

12-24

12-24

12-24













SMART) **ALARM**®

MODEL	ТҮРЕ	VOLTS	DECIBELS	AMPS	WARRANTY	<b>DUTY RATING</b>
EA9724	Smart, Multi-Frequency	12-24	77-97	0.7	ECCOLIFE	Heavy
EA9780	Smart, Multi-Frequency	36-80	77-97	0.8	ECCOLIFE	Heavy
EA9070	Smart, Multi-Frequency	12-24	87-107	0.9	ECCOLIFE	Heavy

**DECIBELS** 

77-97

82-102

82-102

82-102

82-107

82-107

87-112

87-112

87-112

97-112

#### **SMART ALARM® TONAL SURFACE / GROMMET MOUNT**



**TYPE** 

Smart

Smart

Smart

**Smart** 

Smart

Smart

Smart

Smart, Grommet

Smart, Grommet

Smart, OEM Mounting

MODEL

SA951

**SA931N** 

SA950

SA955

**SA901N** 

**SA907N** 

**SA914N** 

**SA917N** 

SA940

SA920



**AMPS** 

0.2

0.2

0.4

0.4

0.3

0.5

1.5

1.5

0.6

0.6



2 Year

2 Year

2 Year

**ECCOLIFE** 

**ECCOLIFE** 

**ECCOLIFE** 

**ECCOLIFE** 

**ECCOLIFE** 

2 Year

**ECCOLIFE** 





WARRANTY **DUTY RATING** Light Light Light Heavy Heavy Heavy

Heavy

Heavy

- World's first self-adjusting back-up alarm, constantly measuring ambient noise and adjusting their sound level, creating a volume that is safe without being annoying or contributing to noise pollution
- Smart Alarms eliminate the need for constant manual adjustment and help prevent intentional alarm disconnection
- Sealed in epoxy for protection against dust, moisture, and vibration



### **FEWER COMMERCIAL** INTERRUPTIONS

Commercial vehicle noise pollution is a growing problem, especially in residential areas and densely populated or confined locations. ECCO's multi-frequency alarms use a range of sound frequencies within a narrow band to emit a warning signal that is perceived to be more directional and to dissipate quicker than a tonal alarm. Keep the peace while complying with OSHA safety standards.

#### Fit the best and forget the rest

ECCO has remained the global market leader in back-up alarms for over 47 years and has more knowledge and experience in the field than any other company. For decades our products and expertise have made us the choice of the world's most prominent OE vehicle manufacturers. We offer an unparalleled range of alarms to suit any application, and all of our alarms feature encapsulated electronics that provide enhanced protection against dust, moisture, and vibration damage. Many of our alarms are so robust they come with an ECCOLIFE™ warranty, guaranteeing the alarm for the life of the vehicle.





#### **SMART ALARM® MULTI-FREQUENCY SURFACE MOUNT**















MODEL	TYPE	VOLTS	DECIBELS	AMPS	WARRANTY	<b>DUTY RATING</b>
EA9724	Smart, Multi-Frequency	12-24	77-97	0.7	ECCOLIFE	Heavy
EA9780	Smart, Multi-Frequency	36-80	77-97	0.8	ECCOLIFE	Heavy
EA9070	Smart, Multi-Frequency	12-24	87-107	0.9	ECCOLIFE	Heavy

#### FIXED DB(A) MULTI-FREQUENCY **SURFACE MOUNT**














MODEL	TYPE	VOLTS	DECIBELS	AMPS	WARRANTY	DUTY RATING
EA5050	Multi-Frequency	12-24	87	0.4	2 Year	Light
EA5200	Multi-Frequency	12-24	97	1.0	2 Year	Light
EA6100	Multi-Frequency	12-24	97	0.7	ECCOLIFE	Medium
EA7020	Multi-Frequency	12-24	102	0.6	ECCOLIFE	Heavy
EA7070	Multi-Frequency	12-24	107	0.8	ECCOLIFE	Heavy

#### **DESIGN FEATURES**

MULTI FREQUENCY\*\*

- Emits sound at multiple frequencies attenuated above 4000Hz
- Warning signal is more directional and perceived to dissipate quicker than pure tone
- Smart Alarm models adjust output to 5dB above surrounding noise
- Sealed in epoxy for protection against dust, moisture, and vibration





APS USA 610 Gateway Center Way, Suites J & K San Diego, CA 92102 USA P: 1 619 263 4164 F: 1 619 263 6814 APS Australia U48 / 9 Vision Street, Wangara, WA 6065 Australia Phone: 61 (8) 9302 2369 Fax: 61 (8) 6305 0047 APS: Singapore Mexico Colombia Chile Perú